

Package: askpass (via r-universe)

March 2, 2025

Type Package

Title Password Entry Utilities for R, Git, and SSH

Version 1.2.1

Description Cross-platform utilities for prompting the user for credentials or a passphrase, for example to authenticate with a server or read a protected key. Includes native programs for MacOS and Windows, hence no 'tcltk' is required. Password entry can be invoked in two different ways: directly from R via the askpass() function, or indirectly as password-entry back-end for 'ssh-agent' or 'git-credential' via the SSH_ASKPASS and GIT_ASKPASS environment variables. Thereby the user can be prompted for credentials or a passphrase if needed when R calls out to git or ssh.

License MIT + file LICENSE

URL <https://r-lib.r-universe.dev/askpass>

BugReports <https://github.com/r-lib/askpass/issues>

Encoding UTF-8

Imports sys (>= 2.1)

RoxygenNote 7.2.3

Roxygen list(markdown = TRUE)

Suggests testthat

Language en-US

Repository <https://r-lib.r-universe.dev>

RemoteUrl <https://github.com/r-lib/askpass>

RemoteRef HEAD

RemoteSha 69c659d8a15721d66ad6468b35dcd7c2758c3ee7

Contents

askpass	2
ssh_askpass	2

Index**3**

askpass	<i>Password Prompt Utility</i>
---------	--------------------------------

Description

Prompt the user for a password to authenticate or read a protected key. By default, this function automatically uses the most appropriate method based on the user platform and front-end. Users or IDEs can override this and set a custom password entry function via the askpass option.

Usage

```
askpass(prompt = "Please enter your password: ")
```

Arguments

prompt the string printed when prompting the user for input.

Details

By default askpass() returns NULL in non-interactive sessions. (These include knitr runs and testthat tests.) If you want to force a password prompt in non-interactive sessions, set the rlib_interactive option to TRUE:

```
options(rlib_interactive = TRUE)
```

Examples

```
# Prompt user for passwd
pw <- askpass("Please enter your password")
```

ssh_askpass	<i>ASKPASS CMD TOOL</i>
-------------	-------------------------

Description

This returns the path to the native askpass executable which can be used by git-credential or ssh-agent. Most users don't have worry about this.

Usage

```
ssh_askpass()
```

Details

On Windows and MacOS the package automatically sets the SSH_ASKPASS and GIT_ASKPASS variables on load (if not already set). If these are set you should be able to run e.g. `sys::exec_wait("ssh-add")` and you should be prompted for a passphrase if your key is protected.

Index

askpass, [2](#)

ssh_askpass, [2](#)