

Package: commonmark (via r-universe)

June 28, 2024

Type Package

Title High Performance CommonMark and Github Markdown Rendering in R

Version 1.9.1

URL <https://docs.ropensci.org/commonmark/>
<https://r-lib.r-universe.dev/commonmark>
<https://github.github.com/gfm/> (spec)

BugReports <https://github.com/r-lib/commonmark/issues>

Description The CommonMark specification defines a rationalized version of markdown syntax. This package uses the 'cmark' reference implementation for converting markdown text into various formats including html, latex and groff man. In addition it exposes the markdown parse tree in xml format. Also includes opt-in support for GFM extensions including tables, autolinks, and strikethrough text.

License BSD_2_clause + file LICENSE

Suggests curl, testthat, xml2

RoxygenNote 7.2.3

Roxygen list(markdown = TRUE)

Language en-US

Encoding UTF-8

Repository <https://r-lib.r-universe.dev>

RemoteUrl <https://github.com/r-lib/commonmark>

RemoteRef HEAD

RemoteSha 1209f2deae59da839e8484edac70c54cf8ce392

Contents

commonmark	2
extensions	4

Index	5
--------------	----------

Description

Converts markdown text to several formats using John MacFarlane's **cmark** reference implementation. Supported output formats include html, latex, groff man, and normalized "commonmark" markdown. In addition the markdown parse tree can be returned in xml format.

Usage

```
markdown_html(  
  text,  
  hardbreaks = FALSE,  
  smart = FALSE,  
  normalize = FALSE,  
  sourcepos = FALSE,  
  footnotes = FALSE,  
  extensions = FALSE  
)
```

```
markdown_xml(  
  text,  
  hardbreaks = FALSE,  
  smart = FALSE,  
  normalize = FALSE,  
  sourcepos = FALSE,  
  footnotes = FALSE,  
  extensions = FALSE  
)
```

```
markdown_man(  
  text,  
  hardbreaks = FALSE,  
  smart = FALSE,  
  normalize = FALSE,  
  footnotes = FALSE,  
  width = 0,  
  extensions = FALSE  
)
```

```
markdown_commonmark(  
  text,  
  hardbreaks = FALSE,  
  smart = FALSE,  
  normalize = FALSE,  
  footnotes = FALSE,
```

```
    width = 0,  
    extensions = FALSE  
  )  
  
  markdown_text(  
    text,  
    hardbreaks = FALSE,  
    smart = FALSE,  
    normalize = FALSE,  
    footnotes = FALSE,  
    width = 0,  
    extensions = FALSE  
  )  
  
  markdown_latex(  
    text,  
    hardbreaks = FALSE,  
    smart = FALSE,  
    normalize = FALSE,  
    footnotes = FALSE,  
    width = 0,  
    extensions = FALSE  
  )
```

Arguments

text	Markdown text
hardbreaks	Treat newlines as hard line breaks. If this option is specified, hard wrapping is disabled regardless of the value given with width.
smart	Use smart punctuation. See details.
normalize	Consolidate adjacent text nodes.
sourcepos	Include source position attribute in output.
footnotes	parse footnotes
extensions	Enables Github extensions. Can be TRUE (all) FALSE (none) or a character vector with a subset of available extensions .
width	Specify wrap width (default 0 = nowrap).

Details

Support for extensions (including tables and autolink) is provided via the Github [fork](#) of cmark. For now these are opt-in and have to be enabled with the `extensions` parameter. See also the manual page on [extensions](#).

When smart punctuation is enabled, straight double and single quotes will be rendered as curly quotes, depending on their position. Moreover `--` will be rendered as `–` (en-dash), `---` will be rendered as `—` (em-dash), and `...` will be rendered as `…` (ellipses).

Examples

```
md <- readLines("https://raw.githubusercontent.com/yihui/knitr/master/NEWS.md")
html <- markdown_html(md)
xml <- markdown_xml(md)
man <- markdown_man(md)
tex <- markdown_latex(md)
cm <- markdown_commonmark(md)
text <- markdown_text(md)
```

extensions

Github CommonMark Extensions

Description

The Github fork of cmark supports several markdown extensions which provide features which are not (yet) in the official commonmark spec.

Usage

```
list_extensions()
```

Details

Currently the following extensions are supported:

- **table** support rendering of tables: [gfm-spec section 4.10](#)
- **strikethrough** via `~sometext~` syntax: [gfm-spec section 6.5](#)
- **autolink** automatically turn URLs into hyperlinks: [gfm-spec section 6.9](#)
- **tagfilter** blacklist html tags: `title textarea style xmp iframe noembed noframes script plaintext`: [gfm-spec section 6.11](#)
- **tasklist** turns certain list items into checkboxes: [gfm-spec section 5.3](#)

See the full spec for [GitHub Flavored Markdown](#).

Examples

```
print(list_extensions())
```

Index

`commonmark`, [2](#)

`extensions`, [3](#), [4](#)

`list_extensions` (`extensions`), [4](#)

`markdown` (`commonmark`), [2](#)

`markdown_commonmark` (`commonmark`), [2](#)

`markdown_html` (`commonmark`), [2](#)

`markdown_latex` (`commonmark`), [2](#)

`markdown_man` (`commonmark`), [2](#)

`markdown_text` (`commonmark`), [2](#)

`markdown_xml` (`commonmark`), [2](#)